

SKG-IKOB PRODUCTCERTIFICATE

404.611.01

Date of issue: 10-05-2022



Certificate holder

Fuhr GmbH & Co KG
Carl Fuhr Straße 12
D-42579 Heiligenhaus
T: +49 (0) 2056 5920
E: info@fuhr.de
I: www.fuhr.de



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

keeper set

delivered under logo / brand:

FUHR

delivered under type- and / or article number:

type 3/4/10/11 - SKG2
RFP xxxx + RC xxxx
RFP + RJV xxxx Z
RL xxxx P
RL xxxx Z
xxxx = profiel type

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, appearing to be "H.A.J. van Dartel", written over a light blue horizontal line.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

CERTIFICATE

SKG-IKOB PRODUCTCERTIFICATE

Fuhr GmbH & Co KG
Number: 404.611.01

page 2 of 2

1. PRODUCT
keeper set

PRODUCT TYPE
lock striker plate

2. TECHNICAL SPECIFICATION

Operating: N.A.
Construction: 1 keeperplate OR keeperstrip with OR without keeper(s)
System: keeperplate:
single hole for additional hooke bolt
keeperstrip:
2 holes for additional hooke bolt + double hole for latch and square bolt
Material: keeperplate:
plate steel chromate coated
keeperstrip: steel zinc keeper: zamac
Dimension: keeperplate:
flat OR U-profile: 200x20~53x2,8~3,0 mm
keeperstrip:
1539x20~53x2,8~3,0 mm
Fixing: keeperplate:
4 parkers Ø 4 mm, with 2 pcs in steel reinforcement min. 1,5 mm
keeperstrip:
16X Ø 4 mm in steel reinforcement min. 1,5 mm
Intended use: PVC, door-inward-opening, door-outward-opening
in combination with FUHR multipoint locks with additional hook bolts

3. DELIVERY

The delivery includes an installation instruction:
M2-SKG-DE-NL_08_19-4

4. PERFORMANCES

A keeper set according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this keeper set is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this keeper set is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).
